



# Vitra Fix JOINT CLEANER

Liquid joint filler cleaner

## DESCRIPTION

Specially formulated for fast and effective cleaning and removal of stains and dirt on joint fillers, tile ceramic applications, and joint filler residues left on the tile. For general use, it is ideal for removing dirt, lime and detergent residues that accumulate between tiles over time without causing abrasion in the joints.

## AREAS OF USE

- For easy cleaning of cement and lime based mortar residues left on the surface after applications such as adhesives, joint fillers, plaster etc,
- Removal of wax residues on ceramic coatings,
- Ideal for use on acid resistant ceramic tiles, granite tiles, etc.

## ÖZELLİKLER

Color : Transparent  
Ph : 1,5  
Density : 0,9 gr/cm<sup>3</sup>  
Freezing point : -6 °C

## PACKAGING

In 0.5 lt plastic spray packages (10 pieces per box)

## CONSUMPTION

50 linear meters of joint line can be cleaned with 0.5 lt.

## STORAGE AND SHELF LIFE

- It should be stored in moisture-free, dry and protected against external weather conditions.
- Shelf life is 1 year under appropriate storage conditions.
- Opened packages should be kept tightly closed.
- The product should not be exposed to sun or frost during storage.
- It should be stored at temperatures between +0 °C - +40 °C.

## APPLICATION

- It is recommended to apply consecutively in small areas of 3 or 4 tiles.
- Apply directly to the joints.
- Wait maximum 3 minutes for it to penetrate the surface.
- Remove the dirt with a sponge with plenty of water.
- If the dirt is not removed, the dirt is removed by rubbing the dirty surface with a brush, sponge or similar material.
- After removing the dirt, the surface should be rinsed thoroughly.

## SAFETY INSTRUCTIONS

- Since it is acidic, it should not be inhaled and contact with skin and eyes should be avoided.
- It is recommended to use appropriate work equipment (gloves, goggles, mask, knee pads, etc.) during product application.
- Please read the Material Safety Data Sheet (MSDS) for more detailed safety information.

**Note:** Technical values and application instructions are the results of our experience and tests carried out in accordance with international standards, valid under ambient conditions of 23°C and 50% relative humidity.

- Easy implementation
- Fast and effective cleaning
- Special formula that does not corrode joint fillers





SURFACE CLEANING AND MAINTENANCE MATERIALS